



# ***MITSUBISHI ELECTRIC AUTOMATION, INC.***

## ***PLK-E2010R (Rotary Hook)***



### **SPECIFICATIONS**

Stitch Type	Single Needle Lockstitch	Hook	Rotary/Large/Bobbin Size M
Max. Number of Sewing Patterns Possible	255 (Internal Memory) 224 (Floppy Disk)	X/Y Drive	Timing Belt
Sewing Area	(X) 7 <sup>7</sup> / <sub>8</sub> " x (Y) 4"	Needle	135 x 17 Size 18 (Standard)
Max. Sewing Speed	2300 RPM	Work Holder Lift	Max. 25mm
Sewing Speed Selection	200~2000 RPM (10 Steps Variable)	Presser Foot Lift	Max. 18mm
Feeding System	Intermittent or Continuous	Pattern Input	Touch Screen (PLK-E-PAL)
Stitch Length	0.1~12.7mm	Drive Motor	Limi-Servo (550 Watts)
Pattern Storage	Internal Memory or Floppy Disk	Power	220 Volt 3 Phase or Single Phase
Max. Number of Stitches	8,000 Per Pattern	Power	110 Volt (Optional)
Scale Up/Scale Down	10~200% For X and Y Axis	Clamp (Air)	Single Stage
Measurement	W(1200mm) D(920mm) H(1170mm)	Total Weight (Net)	136kg

**NOTE:** Sewing speed may be limited by the type of operation, material, or clamp weight.

**INDUSTRIAL SEWING EQUIPMENT  
ASAP GROUP  
1000 NOLEN DRIVE  
SUITE 200  
GRAPEVINE, TEXAS 76051**

**MAIN: 817.416.9767  
FAX: 817.416.1439  
E-MAIL: [ism@meau.meau.com](mailto:ism@meau.meau.com)  
WEBSITE: [www.meau.com](http://www.meau.com)**